



Stainless Steel Flue Flapper Valve Fuel Damper Valve Suppliers

Our Product Introduction

for more products please visit us on fbballvalve.com

Basic Information

- Place of Origin: China
- Brand Name: FABIA
- Certification: ISO9001, CE, CCS, DNV
- Model Number: 1/8 inch 36 inch
- Minimum Order Quantity: 1 set
- Price: Negotiable
- Packaging Details: Cartons/Wooden cases
- Delivery Time: 15-30 work days
- Payment Terms: L/C, D/A, D/P, T/T, MoneyGram, Western Union
- Supply Ability: 100-1000 set per week





Product Specification

- Product Name: Flue Flapper Valve
- ValveType: Damper Valve
- Material: Stainless Steel
- ActuatorType: Pneumatic
- Application: Petroleum, Chemical, Power, Etc.
- ControlMode: Manual/Pneumatic
- SealType: Stainless Steel
- FlowRate: 2.5m³/h
- Fluid: Air
- Pressure: 1.6Mpa
- Temperature: 1000
- Highlight: damper valve suppliers, fuel damper valve, Stainless Steel Flue Flapper Valve



More Images



Product Description

FABIA Flue Flapper Valve Stainless Steel Flue Flapper Valve

1. Description:

Flue gas baffle valve is mainly used in the inlet, outlet or bypass flue of the absorption tower of the flue gas desulfurization system to isolate the flue gas flow, and can also be used in other flue gas pipelines with relatively high isolation requirements.

Scope of application: chemical, petroleum, metallurgy, paper, pharmaceutical and other industries.

Flue baffle valve is mainly used in boiler flue fan outlet, high temperature resistance, fast opening, pressure resistance without deformation.

2. Specification:

FABIA Valve Parameter List	
Valve type:	Flue Flapper Valve Stainless Steel Flue Flapper Valve
Size:	1/8 inch 18 inch
Material:	WCB,GGG40,FCD,SS304,SS304L,SS316,SS316L,ST37(Q235B),S410
Connection type:	Butt /Flange Connection
Driving model:	Manual/Worm gear drive/Pneumatic/Electric
Pressure rating:	PN0.1 PN16
Temperature:	-40 1000
Model:	FB-DB.....

3. Features:

When working normally, the switch is flexible, no jamming phenomenon, and the resistance is small.
After closing, there is no internal leakage, leakage, good sealing, no air leakage, air leakage phenomenon.
Opening and closing signals are connected with DCS to achieve online monitoring.
Easy operation, short installation period, can be completed in the minor repair period.
Long service life, a basic installation does not need maintenance.
New type of hydraulic drive, high stability.
No deformation at high temperature, no soot collection.
Flange bolts are used to connect with the flue, easy to install and disassemble.
Production process conforms to relevant industry standards.
Use of special sealing materials, patented technology, good sealing performance, wear resistance.





Fabia Valve Industry (Suzhou) Co., Ltd.

+8618913247051/+8618912658215/+8618260178084

sales@fabia-china.com

fbballvalve.com

Room 1305, Building 3, Jundi Business Plaza, No.3, Weihua Road, Suzhou Industrial Park